Nye Lubricants TECHNOLOGY IN MOTION*

SAFETY DATA SHEET

1. Identification

Product identifier NYOGEL 774F-MS

Other means of identification

Product Code NYOGEL 774F-MS
Recommended use Lubricating Grease
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name

Address

Nye Lubricants, Inc.

12 Howland Road
Fairhaven, MA 02719

United States

Telephone General Assistance +1-508-996-6721

Websitewww.nyelubricants.comE-mailsds@nyelubricants.comContact personNye Lubricants EH&S

Emergency phone number 3E Online +1-800-451-8346

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Reproductive toxicity Category 2

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of damaging fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response IF exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
1-Decene, homopolymer, hydrogenated		68037-01-4	10 - < 20
1-DODECENE POLYMER WITH 1-DECENE, HYDROGENATED		151006-60-9	10 - < 20
1-DODECENE, POLYMER WITH 1-DECENE AND 1-OCTENE, HYDROGENATED		163149-28-8	10 - < 20

Material name: NYOGEL 774F-MS SDS CANADA

NYOGEL 774F-MS Version #: 04 Revision date: November-15-2023 Issue date: December-29-2015

Chemical name	Common name and synonyms	CAS number	%
MOLYBDENUM DISULFIDE		1317-33-5	5 - < 10
ALKYLATED DIPHENYLAMINE		Trade Secret	< 1
Other components below reporta	ble levels		30 - < 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

General fire hazards

Do not use water jet as an extinguisher, as this will spread the fire.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use water spray to cool unopened containers.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up **Environmental precautions**

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
MOLYBDENUM DISULFIDE (CAS 1317-33-5)	TWA	3 mg/m3	Respirable fraction.

Material name: NYOGEL 774F-MS NYOGEL 774F-MS Version #: 04 Revision date: November-15-2023 Issue date: December-29-2015

US	ACGIH	Threshold	Limit Values

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components TWA 3 mg/m3 Total Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) TO mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM TWA 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Walue MOLYBDENUM TWA 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value MOLYBDENUM TWA 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components No biological exposure limits noted for the ingredient(s). Good general veritiation should be used. Verillation rates should be matched to conditions, if maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels below recommended. Skin protection Hand protection Hand protection Hand protection Hand protection Hand protection Use of an impervious agron is recommended. Wear appropriate chemical resistant gloves. Use of an impervious agron is recommended. Wear appropriate thermal protective clothing, when necessary.	US. ACGIH Threshold Lim Components	Туре	Value	Form
Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) TWA 3 mg/m3 Respirable. DISULFIDE (CAS 1317-33-5) 10 mg/m3 Total Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) TWA 3 mg/m3 Respirable. MOLYBDENUM DISULFIDE (CAS 1317-33-5) TWA 3 mg/m3 Respirable fraction. MOLYBDENUM DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable fraction. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) TWA 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) TWA 10 mg/			10 mg/m3	Inhalable fraction.
MOLYEDENUM DISULFIDE (CAS 1317-33-5) TWA 3 mg/m3 Total Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Form MOLYEDENUM MOLYEDENUM TWA 3 mg/m3 Respirable. DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYEDENUM MOLYEDENUM TWA 3 mg/m3 Respirable. DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable fraction. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYEDENUM DISULFIDE (CAS 1317-33-5) TWA 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) Components Type Value Form MOLYEDENUM DISULFIDE (CAS 1317-33-5) TWA 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) Roll of mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) Roll o	•	•	•	_
DISULFIDE (CAS 1317-33-5) Total Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Total Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Total Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Total Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) TWA TWA TWA TWA TWA TWA TWA TO mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components No biological exposure limits noted for the ingredient(s). Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use processe enclosures, local exhaust ventilation, or other engineering rorl for the protection Wear appropriate chemical resistant gloves. Vidual protection measures, such as personal protective equipment Eye/face protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	Components	Туре	Value	Form
Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) TO mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) TO mg/m3 Inhalable fraction. TWA TWA TWA TWA TWA TWA TWA TWA TWA TW	DISULFIDE (CAS	TWA	3 mg/m3	Respirable.
Safety Regulation 296/97, as amended) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable fraction. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable fraction. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) B hour 10 mg/m3 Inhalable fraction. Ogical limit values No biological exposure limits noted for the ingredient(s). Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits flexposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.			10 mg/m3	Total
MOLYBDENUM DISULFIDE (CAS 1317-33-5) TWA 3 mg/m3 Respirable. 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable fraction. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components TWA 10 mg/m3 DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Roada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Roada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Roada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Roada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Roada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Roada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Roada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table			Chemical Substances, O	ccupational Health and
DISULFIDE (CAS 1317-33-5) Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable fraction. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Outario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) B hour 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Origical limit values ropriate engineering toris No biological exposure limits noted for the ingredient(s). Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	Components	Туре	Value	Form
Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form Inhalable fraction. Osigical limit values Rood general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels below recommended exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer e	DISULFIDE (CAS	TWA	3 mg/m3	Respirable.
MOLYBDENUM			10 mg/m3	Inhalable
MOLYBDENUM DISULFIDE (CAS 1317-33-5) 10 mg/m3 Inhalable fraction. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components TWA 10 mg/m3 Inhalable fraction. MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components TWA 10 mg/m3 DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Ogical limit values ropriate engineering rols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.				_
DISULFIDE (CAS 1317-33-5) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components TWA 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Ogical limit values ropriate engineering frois Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	Components	Туре	Value	Form
Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Origical limit values ropriate engineering Irols No biological exposure limits noted for the ingredient(s). Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	DISULFIDE (CAS	TWA	3 mg/m3	Respirable fraction.
Components Type MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components TWA 10 mg/m3 Inhalable fraction. MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Origical limit values ropriate engineering trols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Widual protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	,		10 mg/m3	Inhalable fraction.
DISULFIDE (CAS 1317-33-5) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Ogical limit values ropriate engineering rols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.				Form
Components Type Value MOLYBDENUM DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Ogical limit values ropriate engineering trols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	DISULFIDE (CAS	TWA	10 mg/m3	Inhalable fraction.
DISULFIDE (CAS 1317-33-5) Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Ogical limit values No biological exposure limits noted for the ingredient(s). Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.			=	afety)
Components Type Value Form MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. Ogical limit values ropriate engineering trols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	DISULFIDE (CAS	TWA	10 mg/m3	
MOLYBDENUM DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. ogical limit values ropriate engineering trols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	Canada. Saskatchewan Ol	ELs (Occupational Health and Safety Regu	ulations, 1996, Table 21)	
DISULFIDE (CAS 1317-33-5) 8 hour 10 mg/m3 Inhalable fraction. ogical limit values ropriate engineering trols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	Components	Туре	Value	Form
No biological exposure limits noted for the ingredient(s). Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Hand protection Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	DISULFIDE (CAS	15 minute	20 mg/m3	Inhalable fraction.
Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection If contact is likely, safety glasses with side shields are recommended. Skin protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	,	8 hour	10 mg/m3	Inhalable fraction.
Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection By the process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment If contact is likely, safety glasses with side shields are recommended. Skin protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. In case of insufficient ventilation, wear suitable respiratory equipment.	ogical limit values	No biological exposure limits noted for the	e ingredient(s).	
Eye/face protection Skin protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	ropriate engineering	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been		
Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.				d.
Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.		Wear appropriate chemical resistant glov	res.	
	Other	Use of an impervious apron is recommen	nded.	
	Respiratory protection	In case of insufficient ventilation, wear su	itable respiratory equipmer	nt.
	* * *		* * * *	

Material name: NYOGEL 774F-MS

SDS CANADA







General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Solid.

Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point Initial boiling point and boiling

range

Flash point

4307 °F (2375 °C) estimated 842 °F (450 °C) estimated

> 392.0 °F (> 200.0 °C) ASTM D-92

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits
Explosive limit - lower (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density0.93 g/cm³Explosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Shelf life4 years

Specific gravity 3.83 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: NYOGEL 774F-MS

SDS CANADA

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

MOLYBDENUM DISULFIDE (CAS 1317-33-5)

<u>Acute</u>

Inhalation

LC50 Rat 2820 mg/l/4h

Skin corrosion/irritation

Serious eye damage/eye

irritation

Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not available.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

No data is available on the degradability of any ingredients in the mixture.

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: NYOGEL 774F-MS

NYOGEL 774F-MS Version #: 04 Revision date: November-15-2023 Issue date: December-29-2015

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the or

16. Other information

Issue date December-29-2015

Material name: NYOGEL 774F-MS SDS CANADA

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision date November-15-2023

Version # 04

List of abbreviations AICIS: Australian Inventory of Industrial Chemicals.

Disclaimer Nye Lubricants, Inc. cannot anticipate all conditions under which this information and its product,

or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.

Revision information Product and Company Identification: Physical States

Fire-fighting measures: Fire fighting equipment/instructions

Accidental release measures: Methods and materials for containment and cleaning up

Exposure controls/personal protection: Eye/face protection Exposure controls/personal protection: Respiratory protection

Exposure controls/personal protection: PPE Symbols

Physical and chemical properties: Form

Physical and chemical properties: Flammability (solid, gas)

Toxicological information: Acute toxicity

Ecological information: Bioaccumulative potential

Material name: NYOGEL 774F-MS SDS CANADA