SAFETY DATA SHEET



1. Identification

Product identifier FUCHS TIM PUTTY 3W

Other means of identification None.

Recommended use Thermal Conductive Gap Filler

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name

Nye Lubricants, Inc.

A Member of the FUCHS Group

Address 12 Howland Road

Fairhaven, MA 02719

USA

 Telephone
 +1 508 996 6721

 E-mail
 sds@fuchs.com

Emergency telephone

number

+1 866 519 4752

Access code 334212

Website www.nyelubricants.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Reproductive toxicity (fertility) Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of damaging fertility.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ALUMINIUM OXIDE		1344-28-1	60 - < 70
ZINC OXIDE		1314-13-2	20 - < 30

Material name: FUCHS TIM PUTTY 3W 6923 Version #: 01 Issue date: March-11-2025

CAS number % Chemical name Common name and synonyms BENZENAMINE, N-PHENYL-, 68411-46-1 < 0.2 REACTION PRODUCTS WITH 2,4,4-TRIMETHYLPENTENE Other components below reportable levels 10 - < 20

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion Direct contact with eyes may cause temporary irritation. Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice **General information** (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Suitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire. Unsuitable extinguishing media

Specific hazards arising from During fire, gases hazardous to health may be formed.

the chemical Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Special protective equipment

and precautions for firefighters Fire fighting Use water spray to cool unopened containers. equipment/instructions

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear protective equipment and appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, emergency procedures see section 8 of the SDS.

Methods and materials for containment and cleaning up 13 of the SDS.

Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions**

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal

protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, Section 10 of the SDS). including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see

Storage class (TRGS 510): 11 (Combustible solids that cannot be assigned to any of the above storage classes)

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Material name: FUCHS TIM PUTTY 3W SDS US 2/8

ALUMINIUM OXIDE (CAS 1344-28-1) ALUMINIUM OXIDE (CAS 1344-28-1) PEL 5 mg/m3 Total dust. ZINC OXIDE (CAS 1314-13-2) US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000) Components ALUMINIUM OXIDE (CAS 1344-28-1) Type	Components	issible Exposure Limits (PEL) for Air Co Type	Value	Form
1344-28-1		**		-
ZINC OXIDE (CAS 1314-13-2) VINC OXIDE (CAS 1314-13-2) VINC OXIDE (CAS 1344-28-1) ALUMINIUM OXIDE (CAS 1344-28-1) VINC OXIDE (CAS 1344-28-1) VINC OXIDE (CAS 1344-28-1) VINC OXIDE (CAS 1344-28-1) VINC OXIDE (CAS 1344-13-2) VINC OXIDE (CAS 1544-13-2) VINC OXIDE (CAS 1544-13-2		PEL	5 mg/m3	Respirable fraction.
US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000) Components ALUMINIUM OXIDE (CAS TWA 5 mg/m3 Total dust. 15 mg/m3 Total dust. 5 mg/m3 Respirable fraction. 15 mg/m3 Total dust. 50 mpcf Total dust. 50 mpcf Total dust. 15 mpcf Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Total dust. 15 mpcf Respirable fraction. 15 mg/m3 Total dust. 15 mpcf Respirable fraction. 15 mg/m3 Respirable fraction. 10 mg/m3 Respirable fraction. 11 mg/m3 Respirable fraction. 11 mg/m3 Respirable fraction. 11 mg/m3 Respirable fraction. 12 mg/m3 Respirable fraction. 13 mg/m3 Respirable fraction. 13 mg/m3 Respirable fraction. 14 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 16 mg/m3 Respirable fraction. 18 mg/m3 Respirable fraction. 19 mg/m3 Respirable fraction. 19 mg/m3 Respirable fraction. 10 mg/m3 Respirable fraction. 10 mg/m3 Respirable fraction. 10 mg/m3 Respirable fraction. 11 mg/m3 Respirable fraction. 12 mg/m3 Respirable fraction. 13 mg/m3 Respirable fraction. 14 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 16 mg/m3 Respirable fraction. 17 mg/m3 Respirable fraction. 18 mg/m3 Respirable fraction. 19 mg/m3 Respirable fraction. 10 mg/m3 Respirable fraction. 11 mg/m3 Respirable fraction. 12 mg/m3 Respirable fraction. 13 mg/m3 Respirable fraction. 14 mg			15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values (TLV) Components US. ACGIH Threshold Limit Values (TLV) TWA 2 mg/m3 Respirable fraction. Nologinal Components US. ACGIH Threshold Limit Values (TLV) US. ACGIH Threshold Li		PEL	5 mg/m3	Respirable fraction.
US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000) Type Type TWA 5 mg/m3 Total dust. 15 mg/m3 Total dust. 15 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 2INC OXIDE (CAS 1314-13-2) TWA 5 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Respirable fraction. 15 mg/m3 Total dust. 15 mg/m3 Respirable fraction. 15 mg/m3 Total dust. 50 mppof Total dust. 50 mppof Total dust. 15 mg/m3 Respirable fraction. US. ACGIH Threshold Limit Values (TLV) Components Type Value Form US. ACGIH Threshold Limit Values (TLV) Type Value Form US. ACGIH Threshold Limit Values (TLV) Type Value Form US. ACGIH Threshold Limit Values (TLV) Components Type Value Form NOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value TWA 2 mg/m3 Respirable fraction. NOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value TWA 5 mg/m3 Dust. Dust. STEL 10 mg/m3 Fume. 5 mg/m3 Dust. TWA 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). STEL 10 mg/m3 Fume. 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient (s). Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process endosures, local exhaust ventilation, or other engine gondrost to maintain airborne levels below recommended exposure limits. If exposure limits have not beet established, maintain airborne levels below recommended exposure limits. If exposure limits have not beet established protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	1011 10 2)		5 mg/m3	Fume.
ALLUMINIUM OXIDE (CAS 1 TWA 5 mg/m3 Respirable fraction. 1344-28-1) TWA 5 mg/m3 Total dust. 50 mppcf Total dust. 15 mg/m3 Respirable fraction. 15 mg/m3 Total dust. 15 mg/m3 Total dust. 15 mg/m3 Total dust. 15 mg/m3 Respirable fraction. 15 mg/m3 Dust. 15 mg/m3			15 mg/m3	Total dust.
1314-28-1) 15 mg/m3 Total dust. 50 mppcf Total dust. 15 mg/m3 Respirable fraction. 2INC OXIDE (CAS 114-13-2) 15 mg/m3 Total dust. 50 mppcf Total dust. 15 mg/m3 Total dust. 50 mppcf Total dust. 15 mppcf Respirable fraction. US. ACGIH Threshold Limit Values (TLV) Components Type Value Form ZINC OXIDE (CAS STEL 10 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value ZINC OXIDE (CAS IDLH 500 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value ZINC OXIDE (CAS IDLH 500 mg/m3 Intervalues) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS IDLH 5 mg/m3 Dust. STEL 10 mg/m3 Fume. STEL 10 mg/m3 Fume. STEL 10 mg/m3 Fume. STEL 10 mg/m3 Dust. Ogical limit values Occupational Exposure limits noted for the ingredient(s). Ogical limit values Occupational Exposure limits noted for the ingredient(s). Good general ventillation should be used. Ventillation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits if exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection Measures, such as personal protective equipment Eye/face protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventillation, wear suitable respiratory equipment.		• • • • • • • • • • • • • • • • • • • •	•	•
TWA 5 mg/m3 Total dust. TWA 5 mg/m3 Respirable fraction.		TWA	5 mg/m3	Respirable fraction.
ZINC OXIDE (CAS 1314-13-2) US. ACGIH Threshold Limit Values (TLV) Type US. ACGIH Threshold Limit Values (TLV) Type US. ACGIH Threshold Limit Values (TLV) Type Value Form ZINC OXIDE (CAS 1314-13-2) TWA 2 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value ZINC OXIDE (CAS 1DLH 5000 mg/m3 Respirable fraction. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Type Value Value TWA 5 mg/m3 Dust. TWA 5 mg/m3 Fume. TWA 5 mg/m3 Fume. TWA 5 mg/m3 Dust. TWA 5 mg/m3 Dust. TWA 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation, or other engineering tons in airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	1344-20-1)		15 mg/m3	Total dust.
ZINC OXIDE (CAS 1314-13-2) 15 mg/m3 Total dust. 50 mppcf Total dust. 15 mppcf Respirable fraction. 15 mppcf Total dust. 15 mppcf Respirable fraction. 15 mppcf Total dust. 15 mppcf Respirable fraction. 15 mppcf Respi			50 mppcf	Total dust.
1314-13-2) 15 mg/m3 Total dust. 50 mpper Total dust. 15 mpper Respirable fraction. US. ACGIH Threshold Limit Values (TLV) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) TWA 2 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value ZINC OXIDE (CAS 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. TWA 5 mg/m3 Dust. Occupational Exposure Limits are not relevant to the current physical form of the product. Forpitate engineering trois Form Components Cocupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits have not beer established, maintain airborne levels below recommended exposure limits have not beer established, maintain airborne levels below recommended exposure limits have not beer established, maintain airborne levels below recommended exposure limits have not beer established, maintain airborne levels below recommended exposure limits have not beer established, maintain airborne levels below recommended exposure limits have not beer established. Skin protection Mear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection			15 mppcf	Respirable fraction.
15 mg/m3 Total dust. 50 mppcf Total dust. 50 mppcf Total dust. 15 mppcf Respirable fraction. 10 mg/m3 Respirable fraction. 1314-13-2) TWA 2 mg/m3 Respirable fraction. 1314-13-2) TWA 2 mg/m3 Respirable fraction. 1314-13-2) TWA 2 mg/m3 Respirable fraction. 1314-13-2) TWA TW		TWA	5 mg/m3	Respirable fraction.
US. ACGIH Threshold Limit Values (TLV) Components Type Value Form Type Value Form Total dust. Respirable fraction. Walue Type TWA 2 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value Value Value NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value Value Value Value Value SINC OXIDE (CAS 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form TWA 5 mg/m3 Dust. TWA 5 mg/m3 Fume. 5 mg/m3 Dust. Occipational Exposure limits noted for the ingredient(s). Source guidelines Occupational Exposure Limits are not relevant to the current physical form of the product. ropriate engineering frois applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Valual protection measures, such as personal protective equipment Eyelface protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.			15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values (TLV) Components Type Value Form Type Value Form TWA 2 mg/m3 Respirable fraction. TWA 2 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value ZINC OXIDE (CAS 1314-13-2) IDLH 500 mg/m3 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. TWA 5 mg/m3 Dust. STEL 10 mg/m3 Fume. 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.			· ·	Total dust.
US. ACGIH Threshold Limit Values (TLV) Components Type Value Form INIO SIDE (CAS 1314-13-2) TWA 2 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value ZINC OXIDE (CAS 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form INIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form STEL 10 mg/m3 Pume. TWA 5 mg/m3 Dust. STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. Occupational Exposure Limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. Torpriate engineering trols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.			• •	Respirable fraction.
Components Type Value TWA TWA TWA TWA TWA TWA TWA TW	US ACCIU Throchold Lin	sit Values (TLV)		•
TWA 2 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value ZINC OXIDE (CAS 2 IDLH 500 mg/m3 314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 2 Ceiling 15 mg/m3 Dust. STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection Hand protection Hand protection Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.		• •	Value	Form
NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value IDLH 500 mg/m3 314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Ceiling 15 mg/m3 Dust. STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. Occupational Exposure Limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.		STEL	10 mg/m3	Respirable fraction.
NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value ZINC OXIDE (CAS 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. ropriate engineering Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	1011 10 2)	TWA	2 mg/m3	Respirable fraction.
Components Type Value ZINC OXIDE (CAS 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. STEL 10 mg/m3 Fume. 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). Source guidelines Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	NIOCII Immodiataly Dana	versus to Life or Health (IDLH) Values a	· ·	
ZINC OXIDE (CAS 10LH 500 mg/m3 1314-13-2) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS Ceiling 15 mg/m3 Dust. 1314-13-2) STEL 10 mg/m3 Fume. 5 mg/m3 Dust. 15 mg/m3 Dust. 10 mg/m3 Fume. 15 mg/m3 Dust. 10 mg/m3 Dus		•		
US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form ZINC OXIDE (CAS 1314-13-2) STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection If contact is likely, safety glasses with side shields are recommended. Skin protection Hand protection Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	ZINC OXIDE (CAS		500 mg/m3	
Components Type Value Form ZINC OXIDE (CAS 1314-13-2) Ceiling 15 mg/m3 Dust. STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection If contact is likely, safety glasses with side shields are recommended. Skin protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	,	to Chamical Hazarda Basammandad E	vnesure Limite (DEL)	
ZINC OXIDE (CAS 1314-13-2) STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. Occupational Exposure limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.			• • •	Form
STEL 10 mg/m3 Fume. TWA 5 mg/m3 Dust. ogical limit values osure guidelines ropriate engineering trols Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Hand protection Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.				Dust.
TWA 5 mg/m3 Fume. 5 mg/m3 Dust. Ogical limit values Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Hand protection Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.		5	3	
ogical limit values osure guidelines Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection If contact is likely, safety glasses with side shields are recommended. Skin protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.		STEL	10 mg/m3	Fume.
ogical limit values osure guidelines osure guidelines occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection Hand protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.		TWA	5 mg/m3	Fume.
Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection If contact is likely, safety glasses with side shields are recommended. Skin protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.			5 mg/m3	Dust.
Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection If contact is likely, safety glasses with side shields are recommended. Skin protection Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	ogical limit values	No biological exposure limits noted for	r the ingredient(s).	
trols applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level. vidual protection measures, such as personal protective equipment Eye/face protection	_	Occupational Exposure Limits are not	relevant to the current physic	al form of the product.
Eye/face protection Skin protection Hand protection Other Wear appropriate chemical resistant gloves. Use of an impervious apron is recommended. In case of insufficient ventilation, wear suitable respiratory equipment.		Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been		
Hand protection Wear appropriate chemical resistant gloves. Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	-			ed.
Other Use of an impervious apron is recommended. Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.		Wear appropriate chemical resistant of	lloves.	
Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.	-			
		·		nt
	* *			in.







General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. Physical state

Solid. Paste. **Form** Color White.

Not available. Odor **Odor threshold** Not available. Not available. рΗ Melting point/freezing point Not available. Not available. Initial boiling point and boiling

range

Not available. Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Explosive limit - lower (%) Not available. Not available.

Explosive limit - upper (%) Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive. Oxidizing properties Not oxidizing.

2.3 Specific gravity

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Acids. Chlorine.

Hazardous decomposition No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Material name: FUCHS TIM PUTTY 3W 6923 Version #: 01 Issue date: March-11-2025 Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN3077 **UN** number

UN proper shipping name Environmentally hazardous substance, solid, n.o.s. (ZINC OXIDE)

Transport hazard class(es)

9 Subsidiary hazard Ш Packing group **Environmental hazards** Yes 9L **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN3077

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (ZINC OXIDE), MARINE **UN proper shipping name**

POLLUTANT (ZINC OXIDE, Glycine, N-methyl-N-[(9Z)-1-oxo-9-octadecenyl]-)

Transport hazard class(es)

9 Class Subsidiary hazard Packing group Ш **Environmental hazards**


Yes Marine pollutant F-A, S-F **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ZINC OXIDE (CAS 1314-13-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

ı**s** Yes

chemical

Classified hazard

Reproductive toxicity

categories

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Aluminum oxide (fibrous forms) (Alumina)	1344-28-1	60 - < 70	
Zinc Compounds	1314-13-2	20 - < 30	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including CADMIUM, which is known to the State of

California to cause cancer and birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

CADMIUM (CAS ---)
Listed: October 1, 1987
LEAD (CAS ---)
SILICA, CRYSTALLINE (AIRBORNE PARTICLES
Listed: October 1, 1988

OF RESPIRABLE SIZE) (CAS ---)

California Proposition 65 - CRT: Listed date/Developmental toxin

CADMIUM (CAS ---) Listed: May 1, 1997

California Proposition 65 - CRT: Listed date/Male reproductive toxin

CADMIUM (CAS ---) Listed: May 1, 1997 N-HEXANE (CAS 110-54-3) Listed: December 15, 2017

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: FUCHS TIM PUTTY 3W

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

March-11-2025 Issue date

Version # 01

Nye Lubricants, Inc. A Member of the FUCHS Group cannot anticipate all conditions under which Disclaimer

this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and

experience currently available.

Material name: FUCHS TIM PUTTY 3W

6923 Version #: 01 Issue date: March-11-2025