

SAFETY DATA SHEET



1. Identification

Product identifier NYOGEL 756G-EC
Other means of identification None.
Recommended use Lubricating Grease
Recommended restrictions None known.
Manufacturer/Importer/Supplier/Distributor information
Company name Nye Lubricants, Inc.
A Member of the FUCHS Group
Address 12 Howland Road
Fairhaven, MA 02719
USA
Telephone +1 508 996 6721
E-mail sds@fuchs.com

Emergency telephone number +1 866 519 4752
Access code 334212
Website www.nyelubricants.com

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Serious eye damage/eye irritation Category 1
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Causes serious eye damage.
Precautionary statement
Prevention Wear eye protection/face protection.
Response Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage Store away from incompatible materials.
Disposal Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CARBON BLACK		1333-86-4	10 - < 20
PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(2-ETHYLHEXYL AND ISO-BU) ESTERS, ZINC SALTS		68442-22-8	3 - < 5

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC		64742-53-6	< 0.3
DISTILLATES, PETROLEUM, HYDROTREATED LIGHT PARAFFINIC		64742-55-8	< 0.2
Other components below reportable levels			80 - < 90

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Small Spills: Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Do not get this material in contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	PEL	3.5 mg/m3	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
DISTILLATES, PETROLEUM, HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	PEL	5 mg/m3	Mist.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
DISTILLATES, PETROLEUM, HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
CARBON BLACK (CAS 1333-86-4)	IDLH	1750 mg/m3
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	IDLH	2500 mg/m3
DISTILLATES, PETROLEUM, HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	IDLH	2500 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	0.1 mg/m3	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
DISTILLATES, PETROLEUM, HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other


Wear suitable protective clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.



General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Smooth
Physical state	Solid.
Form	Solid. Semi-solid
Color	Black
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.

Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.78 g/cm ³
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Shelf life	4 years

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye damage.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
CARBON BLACK (CAS 1333-86-4)		
<u>Acute</u>		
Oral		
LD50	Rat	> 8000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

CARBON BLACK (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	3 Not classifiable as to carcinogenicity to humans.
DISTILLATES, PETROLEUM, HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes**Classified hazard categories** Serious eye damage or eye irritation**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Zinc Compounds	68442-22-8	3 - < 5

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****California Proposition 65**

WARNING: For more information go to www.P65Warnings.ca.gov. This product can expose you to chemicals including CARBON BLACK and CARBON BLACK EXTRACTS, which is known to the State of California to cause cancer. Certain polycyclic aromatic hydrocarbons (PAHs), arsenic, cadmium, lead, mercury, and nickel may be present on and/or in carbon black and are known as California Proposition 65 listed substances.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ARSENIC (CAS S~AS~I)	Listed: February 27, 1987
CADMIUM (CAS S~CD~C)	Listed: October 1, 1987
CARBON BLACK (CAS 1333-86-4)	Listed: February 21, 2003
CARBON BLACK EXTRACTS (CAS SEQ100239)	Listed: January 1, 1990
LEAD (CAS S~PB~C)	Listed: October 1, 1992
NICKEL (CAS S~NI~C)	Listed: May 7, 2004

California Proposition 65 - CRT: Listed date/Developmental toxin

CADMIUM (CAS S~CD~C)	Listed: May 1, 1997
MERCURY (CAS S~HG~C)	Listed: July 1, 1990

California Proposition 65 - CRT: Listed date/Male reproductive toxin

CADMIUM (CAS S~CD~C)	Listed: May 1, 1997
----------------------	---------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	January-02-2024
Revision date	October-22-2024
Version #	02
Disclaimer	Nye Lubricants, Inc. A Member of the FUCHS Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.