

1. Identification

Product identifier RHEOLUBE 723GR

Other means of identification
Product Code NYOGEL 723GR

Recommended use Lubricating Grease

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Manufacturer

Company name Nye Lubricants, Inc.
Address 12 Howland Road
 Fairhaven, MA 02719
 United States

Telephone General Assistance 508-996-6721
Website www.nyelubricants.com
E-mail sds@nyelubricants.com
Contact person Nye Lubricants EH&S
Emergency phone number 3E Online 800-451-8346

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Reproductive toxicity Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of damaging fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ALKYLATED DIPHENYLAMINE		Trade Secret	1 - < 3*
BARIUM ALKYLNAPHTHALENESULFONAT E		25619-56-1	1 - < 3*

Chemical name	Common name and synonyms	CAS number	%
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC		64742-54-7	1 - < 3
PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC		64742-65-0	1 - < 3
PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC		64741-88-4	1 - < 3
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC		64742-56-9	< 1
Other components below reportable levels			90 - 100

4. First-aid measures

Inhalation	Move to fresh air.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Get medical attention if irritation develops or persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Soak up with inert absorbent material. Clean contaminated surface thoroughly. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Clean up spills immediately, observing precautions in Protective Equipment section. Sweep up and shovel into suitable containers for disposal.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
BARIUM ALKYLNAPHTHALENESULFONATE (CAS 25619-56-1)	PEL	0.5 mg/m ³	
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC (CAS 64742-56-9)	PEL	5 mg/m ³	Mist.
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)	PEL	5 mg/m ³	Mist.
PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	PEL	5 mg/m ³	Mist.
		2000 mg/m ³	
		500 ppm	
PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC (CAS 64741-88-4)	PEL	5 mg/m ³	Mist.
		2000 mg/m ³	
		500 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
BARIUM ALKYLNAPHTHALENESULFONATE (CAS 25619-56-1)	TWA	0.5 mg/m ³	
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC (CAS 64742-56-9)	TWA	5 mg/m ³	Inhalable fraction.
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)	TWA	5 mg/m ³	Inhalable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC (CAS 64741-88-4)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
BARIUM ALKYLNAPHTHALENESULFONATE (CAS 25619-56-1)	TWA	0.5 mg/m3	
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC (CAS 64742-56-9)	STEL	10 mg/m3	Mist.
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)	TWA	5 mg/m3	Mist.
	STEL	10 mg/m3	Mist.
PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	TWA	5 mg/m3	Mist.
	Ceiling	1800 mg/m3	
PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC (CAS 64741-88-4)	STEL	10 mg/m3	Mist.
	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.



General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Liquid. Semi-solid
Color	Tan
Odor	Slight
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	> 392.0 °F (> 200.0 °C) ASTM D-92
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.00001 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.86 g/cm ³
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Kinematic viscosity	80.6 cSt
Kinematic viscosity temperature	104 °F (40 °C)
Oxidizing properties	Not oxidizing.
Pour point	< 104 °F (< 40 °C)
Shelf life	4 years
Specific gravity	0.87 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids, alkalies and oxidizing agents.
Hazardous decomposition products	Carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of sulfur. Methacrylate monomers.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
------------	---------	--------------

PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)

Acute

Dermal

LD50	Rabbit	2000 mg/kg
------	--------	------------

Inhalation

LC50	Rat	2.18 mg/l/4h
------	-----	--------------

Oral

LD50	Rat	2000 mg/kg
------	-----	------------

PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)

Acute

Dermal

LD50	Rabbit	2000 mg/kg
------	--------	------------

Inhalation

LC50	Rat	2.18 mg/l/4h
------	-----	--------------

Oral

LD50	Rat	5000 mg/kg
------	-----	------------

PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC (CAS 64741-88-4)

Acute

Dermal

LD50	Rabbit	2000 mg/kg
------	--------	------------

Inhalation

LC50	Rat	2.18 mg/l/4h
------	-----	--------------

Oral

LD50	Rat	5000 mg/kg
------	-----	------------

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7) 3 Not classifiable as to carcinogenicity to humans.

PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED Known To Be Human Carcinogen.
LIGHT PARAFFINIC (CAS 64742-56-9)
PETROLEUM DISTILLATES, SOLVENT-REFINED Known To Be Human Carcinogen.
HEAVY PARAFFINIC (CAS 64741-88-4)

Reproductive toxicity Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure Not classified.
Specific target organ toxicity - repeated exposure Not classified.
Aspiration hazard Not an aspiration hazard.
Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)		
Aquatic		
Crustacea	EC50 Daphnia	1000.0001, 48 Hours
PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)		
Aquatic		
Crustacea	EC50 Daphnia	1000.0001, 48 Hours
PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC (CAS 64741-88-4)		
Aquatic		
Crustacea	EC50 Daphnia	1000.0001, 48 Hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential No data available.
Mobility in soil No data available.
Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations Dispose in accordance with all applicable regulations.
Hazardous waste code D005: Waste Barium
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT
Not regulated as dangerous goods.
IATA
Not regulated as dangerous goods.
IMDG
Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BARIUM ALKYLNAPHTHALENESULFONATE Listed.
(CAS 25619-56-1)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Reproductive toxicity

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Barium compounds [except BaSO ₄]	25619-56-1	1 - < 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC (CAS 64742-56-9)
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)
PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)
PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC (CAS 64741-88-4)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	December-03-2013
Revision date	February-03-2023
Version #	07
List of abbreviations	AICIS: Australian Inventory of Industrial Chemicals.
Disclaimer	Nye Lubricants, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.