SAFETY DATA SHEET



1. Identification

Product identifier WATCH OIL 140C

Other means of identification

Product Code WATCH OIL 140C
Recommended use Lubricating Oil
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Company name
Nye Lubricants, Inc.

A Member of the FUCHS Group

Address 12 Howland Road

Fairhaven, MA 02719

USA

 Telephone
 +1 508 996 6721

 E-mail
 sds@fuchs.com

Emergency telephone

number

+1 866 519 4752

Access code 334212

Website www.nyelubricants.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
WHITE MINERAL OIL		8042-47-5	40 - < 50
PHENOL, 4,4'-METHYLENEBIS[2,6-BIS IMETHYLETHYL)]-	(1,1-D	118-82-1	< 1
Other components below reportable levels			50 - < 60

 4. First-aid measures

Inhalation Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Get medical attention if irritation develops or persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis.

Indication of immediate medical attention and special

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

treatment needed
General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemicals. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters
Fire fighting

Cool containers exposed to heat with water spray and remove container, if no risk is involved.

equipment/instructions Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Will burn if involved in a fire. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material. Clean contaminated surface thoroughly.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Clean up spills immediately, observing precautions in Protective Equipment section. Sweep up and shovel into suitable containers for disposal.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly

after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000) Components Type Value Form

WHITE MINERAL OIL (CAS PEL 5 mg/m3 Mist. 8042-47-5)

Material name: WATCH OIL 140C

US. ACGIH Threshold Limit Values (TLV)

Form Components Value Type WHITE MINERAL OIL (CAS TWA Inhalable fraction. 5 mg/m3

8042-47-5)

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components Type Value WHITE MINERAL OIL (CAS **IDLH** 2500 mg/m3

8042-47-5)

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Form Components Type WHITE MINERAL OIL (CAS STFL 10 mg/m3 Mist. 8042-47-5) TWA 5 mg/m3 Mist.

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Exposure guidelines This material does not have established exposure limits. Under conditions which may generate

mists, observe the OSHA PEL of 5 mg per cubic meter

Appropriate engineering

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to controls

maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Face shield is recommended. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear suitable protective clothing. Other

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary





General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid. Liquid Color Light yellow. Slight Odor

Odor threshold Not available. pН Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Vapor density

Flash point 347.0 °F (175.0 °C) ASTM D-92

Evaporation rate Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Vapor pressure Not available.

Material name: WATCH OIL 140C SDS US

Not available.

Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient

(n-octanol/water)

Not available.

Not available. Auto-ignition temperature **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density 0.86 g/cm3 **Explosive properties** Not explosive.

Combustible IIIB estimated Flammability class

Flash point class Combustible IIIB Oxidizing properties Not oxidizing. Shelf life 4 years

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Strong oxidizing agents. Strong acids, alkalies and oxidizing agents. Incompatible materials

Hazardous decomposition

products

Carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation. Eye contact

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Test Results Components Species

PHENOL, 4,4'-METHYLENEBIS[2,6-BIS(1,1-DIMETHYLETHYL)]- (CAS 118-82-1)

Acute Oral

LD50 Rat 5000 mg/kg

WHITE MINERAL OIL (CAS 8042-47-5)

Acute Oral

> > 5000 mg/kg LD50 Rat

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eve damage/eve Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Material name: WATCH OIL 140C SDS US 4/7 Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

WHITE MINERAL OIL (CAS 8042-47-5)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

WHITE MINERAL OIL (CAS 8042-47-5)

Aquatic

Fish LC50 Fish > 10000 mg/l, 96 Hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available.

No data available.

Other adverse effects

Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

the IBC Code

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

Material name: WATCH OIL 140C SDS US

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Ye

chemical

Aspiration hazard

Classified hazard categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Inventory name	On inventory (yes/no)*
Australian Inventory of Industrial Chemicals (AICIS)	No
Domestic Substances List (DSL)	No
Non-Domestic Substances List (NDSL)	Yes
Inventory of Existing Chemical Substances in China (IECSC)	Yes
European Inventory of Existing Commercial Chemical Substances (EINECS)	No
European List of Notified Chemical Substances (ELINCS)	No
Inventory of Existing and New Chemical Substances (ENCS)	No
Existing Chemicals List (ECL)	No
New Zealand Inventory	No
Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan Chemical Substance Inventory (TCSI)	Yes
Toxic Substances Control Act (TSCA) Inventory	Yes
	Domestic Substances List (DSL) Non-Domestic Substances List (NDSL) Inventory of Existing Chemical Substances in China (IECSC) European Inventory of Existing Commercial Chemical Substances (EINECS) European List of Notified Chemical Substances (ELINCS) Inventory of Existing and New Chemical Substances (ENCS) Existing Chemicals List (ECL) New Zealand Inventory Philippine Inventory of Chemicals and Chemical Substances (PICCS) Taiwan Chemical Substance Inventory (TCSI)

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue dateJanuary-09-2014Revision dateDecember-10-2025

Version # 04

Material name: WATCH OIL 140C SDS US

Disclaimer

Nye Lubricants, Inc. A Member of the FUCHS Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

Material name: WATCH OIL 140C